

PRELIMINARY LCA STUDY for a following **EPD - ENVIRONMENTAL PRODUCT DECLARATION**

as per ISO 14025 and EN 15804+A2

Bau-EPD
Baustoffe mit Transparenz



OWNER AND PUBLISHER

Bau EPD GmbH, A-1070 Wien, Seidengasse 13/3, www.bau-epd.at

PROGRAMME OPERATOR

Bau EPD GmbH, A-1070 Wien, Seidengasse 13/3, www.bau-epd.at

HOLDER OF THE DECLARATION

Name of declaration holder

DECLARATION NUMBER

To be accorded with Bau EPD GmbH

ISSUE DATE

Date

VALID TO

Date

NUMBER OF DATASETS

Number

ENERGY MIX APPROACH

MARKET BASED APPROACH

Name and description of product

Name of declaration owner

picture

**To be accorded with declaration
owner and Bau EPD GmbH**

**Company logo
of declaration owner**

Content of the preliminary study for an EPD

1	General information	3
2	Product	5
2.1	General product description	5
2.2	Application field	5
2.3	Standards, guidelines and regulations relevant for the product	5
2.4	Technical data	5
2.5	Basic/auxiliary materials	5
2.6	Production	6
2.7	Packaging	6
2.8	Conditions of delivery	6
2.9	Transport	6
2.10	Processing/ installation	6
2.11	Use stage	6
2.12	Reference service life (RSL)	6
2.13	Reuse and recycling	6
2.14	Disposal	6
2.15	Further information	6
3	LCA: Calculation rules	7
3.1	Declared unit/ Functional unit	7
3.2	System boundary	8
3.3	Flow chart of processes/stages in the life cycle	8
3.4	Estimations and assumptions	8
3.5	Cut-off criteria	8
3.6	Data sources	8
3.7	Data quality	8
3.8	Reporting period	8
3.9	Allocation	8
3.10	Comparability	8
4	LCA: Scenarios and additional technical information	9
4.1	A1-A3 product stage	9
4.2	A4-A5 Construction process stage	9
4.3	B1-B7 use stage	10
4.4	C1-C4 End-of-Life stage	11
4.5	D Potential of reuse and recycling	11
5	LCA: results	12
6	LCA: Interpretation	15
7	Literature	15
8	Directory and Glossary	15
8.1	List of figures	15
8.2	List of tables	16
8.3	Abbreviations	16
8.3.1	Abbreviations as per EN 15804	16
8.3.2	Abbreviations as per corresponding PCR	16

1 General information

Product name Name and description of product	Declared Product / Declared Unit Description of the declared product and declared unit/functional unit
Declaration number To be accorded with Bau EPD GmbH	Number of datasets in pre-study Document(s): XX
Declaration data <input type="checkbox"/> Specific data <input type="checkbox"/> Average data	Range of validity The product, the sites/distribution locations and sales location (region, country) on which the data of the LCA study is based must be cited.
Declaration based on: MS-HB Version XX dated TT.MM.YYYY: Name of PCR PCR-Code Version XX dated TT.MM.YYYY (PCR tested and approved by the independent expert committee = PKR-Gremium) Version of EPD-Format-Template M-Dok 14a The owner of the declaration is liable for the underlying information and evidence; Bau EPD GmbH is not liable with respect to manufacturer information, life cycle assessment data and evidence.	In the case of average data sets for preliminary studies on EPDs, reference must be made to this type of data set. The representativeness of the declaration with regard to the production volume covered by the LCA and the technology used must be presented; the range of variation of the product group depicted must also be indicated in the interpretation. If no plants exist as part of the preliminary study or production has not yet started, a brief description of the data basis and calculation used for the assessment must be provided. Points from EN 15804 that cannot be complied with must be quoted and justified. Points from c-PKR and PKR-B that cannot be complied with must be cited and justified.
Type of Declaration as per EN 15804 From cradle to LCA-method: (i.e. cut-off by classification)	Database, Software, Version Declaration of background database, Software used and both its versions Version Characterisation Factors: Quelle, Version
Author of the Life Cycle Assessment Name of the author Institution, Address COUNTRY	The CEN standard EN 15804:2019+A2 serves as the core-PCR. The c-PCR of CEN xxxxxx has been applied. Independent verification of the declaration according to ISO 14025:2010 <input type="checkbox"/> internally <input checked="" type="checkbox"/> externally Verifier 1: Name Verifier 2: Name
Holder of the Declaration Name of the manufacturer/owner Institution Address COUNTRY	Owner, Publisher and Programme Operator Bau EPD GmbH Seidengasse 13/3 1070 Vienna Austria

DI (FH) DI DI Sarah Richter
Head of Conformity Assessment Body

Academic Title Name
Verifier

Academic Title Name,
Verifier

Declaration number of the EPD document

Note: EPDs from similar product groups from different programme operators might not be comparable.

2 Product

2.1 General product description

Content as defined in product specific PCR-B document.

2.2 Application field

Content as defined in product specific PCR-B document.

2.3 Standards, guidelines and regulations relevant for the product

Content as defined in product specific PCR-B document.

2.4 Technical data

Content as defined in product specific PCR-B document.

Table 1: technical data of the declared construction product(s)

Characterization	Value	Unit

2.5 Basic/auxiliary materials

Content as defined in product specific PCR-B document.

Table 2: Basic and auxiliary materials in mass percentage

Components	Function	Mass fraction in percent

2.6 Production

Content as defined in product specific PCR-B document.

2.7 Packaging

Content as defined in product specific PCR-B document.

2.8 Conditions of delivery

Content as defined in product specific PCR-B document.

2.9 Transport

Content as defined in product specific PCR-B document.

2.10 Processing/ installation

Content as defined in product specific PCR-B document.

2.11 Use stage

Content as defined in product specific PCR-B document.

2.12 Reference service life (RSL)

Content as defined in product specific PCR-B document.

Table 3: Reference service life (RSL)

Characterization	value	unit
Mineral insulating slabs in EIFS		years
Other applications of mineral insulating products		years
Reference conditions on which the RSL is based (if relevant)		Individual units

2.13 Reuse and recycling

Content as defined in product specific PCR-B document.

2.14 Disposal

Content as defined in product specific PCR-B document.

2.15 Further information

Content as defined in product specific PCR-B document.

3 LCA: Calculation rules

3.1 Declared unit/ Functional unit

Content as defined in product specific PCR-B document.

Table 4: Declared unit

Characterization	value	unit
Declared unit		
Other information		
Other information		
Other information		
Calculation factor for conversion into kg		-

Table 5: Functional unit

Characterization	value	unit
Functional unit		
Other information		
Other information		
Other information		
Calculation factor for conversion into kg		-

3.2 System boundary

Content as defined in product specific PCR-B document.

Table 6: Declared life cycle stages

PRODUCT STAGE			CON- STRUCTION PROCESS STAGE		USE STAGE							END-OF-LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Construction, installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction, demolition	Transport	Waste processing	Disposal	Reuse- Recovery- Recycling- potential
x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x

X = included in LCA; ND = Not declared

3.3 Flow chart of processes/stages in the life cycle

Content as defined in product specific PCR-B document.

3.4 Estimations and assumptions

Content as defined in product specific PCR-B document.

3.5 Cut-off criteria

Content as defined in product specific PCR-B document.

3.6 Data sources

Content as defined in product specific PCR-B document.

3.7 Data quality

Content as defined in product specific PCR-B document.

3.8 Reporting period

Content as defined in product specific PCR-B document.

3.9 Allocation

Content as defined in product specific PCR-B document.

3.10 Comparability

Declaration number of the EPD document

Content as defined in product specific PCR-B document.

4 LCA: Scenarios and additional technical information

Content as defined in product specific PCR-B document.

4.1 A1-A3 product stage

Content as defined in product specific PCR-B document.

4.2 A4-A5 Construction process stage

Content as defined in product specific PCR-B document.

Table 7: Description of the scenario „Transport to building site (A4)“^{x)}

Parameters to describe the transport to the building site (A4)	Value	Unit
Average transport distance		km
vehicle type, Commission Directive 2007/37/EC (European Emission Standard)		-
Fuel type and average consumption of vehicle		l/100 km
Maximum transport mass		tons
Capacity utilisation (including empty returns)		%
Bulk density of transported products		kg/m ³
Volume capacity utilisation factor (factor: =1 or <1 or ≥ 1 for compressed or nested packaged products)		-

^{x)} The table must be filled with available information from chosen datasets resp. must be adapted (e.g. transport by ship). The used datasets must be indicated in a footnote.

Table 8: Description of the scenario „Installation of the product in the building (A5)“

Parameters to describe the installation of the product in the building (A5)	Value	Unit
Ancillary materials for installation (specified by material);		kg/t t/t l/t
Ancillary materials for installation (specified by type);		-
Water use		m ³ /t l/t
Other resource use		kg/t t/t l/t
Electricity demand		kWh or MJ/t
Other energy carrier(s):		kWh or MJ/t
Wastage of materials on the building site before waste processing, generated by the product’s installation (specified by type)		kg/t
Output materials (specified by type) as result of waste processing at the building site e.g. of collection for recycling, for energy recovery, disposal (specified by route)		kg/t
Direct emissions to ambient air (such as dust, VOC), soil and water		tg/t

4.3 B1-B7 use stage

B1: Content as defined in product specific PCR-B document.

Table 9: Description of the scenario „maintenance (B2)“ based on table 9 in EN 15804

Parameters maintenance (B2)	value	unit
Maintenance process		Description or source where description can be found
Maintenance cycle		Number per RSL or year ^a
Ancillary materials for maintenance, e.g. cleaning agent, specify materials		Kg/cycle
Waste material resulting from maintenance (specify materials)		kg
Net freshwater consumption during maintenance		m ³
Energy input during maintenance, e.g. vacuum cleaning, energy carrier type, e.g. electricity, and amount, if applicable and relevant		kWh

Table 10: Description of the scenario „repair (B3)“

Parameters repair (B3)	value	unit
Repair process		Description or source where description can be found
Inspection process		Description or source where description can be found
Repair cycle		Number per RSL or year
Ancillary materials, e.g. lubricant, specify materials		Kg or kg/cycle
Waste material resulting from repair, (specify materials)		kg
Net freshwater consumption during repair		m ³
Energy input during repair, e.g. crane activity, energy carrier type, e.g. electricity, and amount		kWh

Table 11: Description of scenario „replacement (B4)“

Parameters replacement (B4)	value	unit
Replacement cycle		Number per RSL or year
Energy input during replacement e.g. crane activity, energy carrier type, e.g. electricity and amount if applicable and relevant		kWh
Exchange of worn parts during the product's life cycle, e.g. zinc galvanised steel sheet, specify materials		kg

Table 12: Description of scenario „refurbishment (B5)“

Parameters refurbishment (B5)	value	unit
Refurbishment process		Description or source where description can be found
Refurbishment cycle		Number per RSL or year

Energy input during refurbishment e.g. crane activity, energy carrier type, e.g. electricity, and amount if applicable and relevant		kWh
Material input for refurbishment, e.g. bricks, including ancillary materials for the refurbishment process e.g. lubricant, (specify materials)		kg or kg / cycle
Waste material resulting from refurbishment (specify materials)		kg
Further assumptions for scenario development, e.g. frequency and time period of use, number of occupants		Units as appropriate

Table 13: Description of scenarios „energy (B6)“ resp. „Water (B7)“

Parameters energy (B6) and water (B7)	value	unit
Ancillary materials, e.g. lubricant, specify materials		kg or kg/cycle
Net fresh water consumption		m ³
Type of energy carrier, e.g. electricity, natural gas, district heating		kWh or m ³
Power output of equipment		kW
Characteristic performance, e.g. energy efficiency, emissions, variation of performance with capacity utilisation etc.		units as appropriate
Further assumptions for scenario development, e.g. frequency and period of use, number of occupants		units as appropriate

4.4 C1-C4 End-of-Life stage

Content as defined in product specific PCR-B document.

Table 14: Description of the scenario „Disposal of the product (C1 to C4)“

(Procedures of collection and recovery must be described in a footnote (including technical features)).

Parameters for End-of-Life stage (C1-C4)	value	Quantity per m ³ insulation material
Collection process specified by type		kg collected separately
		kg collected with mixed construction waste
Recovery system specified by type		kg for re-use
		kg for recycling
		kg for energy recovery
Disposal specified by type		kg product or material for final deposition
Assumptions for scenario development, e.g. transportation		Appropriate units

4.5 D Potential of reuse and recycling

Content as defined in product specific PCR-B document.

Table 15: Description of the scenario „re-use, recovery and recycling potential (module D)“

(Substituted primary materials resp. technologies must be declared in a separate footnote (including technical information)).

Parameters for module D	value	unit
Materials for reuse, recovery or recycling from A4-A5		%
Energy recovery or secondary fuels from A4-A5		MJ/t resp. kg/t
Materials for reuse, recovery or recycling from B2-B5		%
Energy recovery or secondary fuels from B2-B5		MJ/t resp. kg/t
Materials for reuse, recovery or recycling from C1-C4		%
Energy recovery or secondary fuels from C1-C4		MJ/t resp. kg/t

5 LCA: results

Table 16: Parameters to describe the environmental impact

Parameter	unit	A1-A3	A4	A5	B1	B2	B5	B6	B7	C1	C2	C3	C4	D
GWP total	kg CO ₂ eq.													
GWP fossil fuels	kg CO ₂ eq.													
GWP biogenic	kg CO ₂ eq.													
GWP luluc	kg CO ₂ eq.													
ODP	kg CFC-11 eq.													
AP	mol H ⁺ eq.													
EP freshwater	kg P eq.													
EP marine	kg N eq.													
EP terrestrial	mol N eq.													
POCP	kg NMVOC eq.													
ADPE	kg Sb eq.													
ADPF	MJ H _u													
WDP	m ³ Welt eq. entz.													
Legende	GWP = Global warming potential; luluc = land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP = Eutrophierungspotenzial; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources WDP = Water (user) deprivation potential, deprivation-weighted water consumption													

Table 17: Additional environmental impact indicators

Parameter	Unit	A1-A3	A4	A5	B1	B2	B5	B6	B7	C1	C2	C3	C4	D
PM	disease incidence													
IRP	kBq U235 eq.													
ETP-fw	CTUe													
HTP-c	CTUh													
HTP-nc	CTUh													
SQP	dimensionless													
Legende	PM = Potential incidence of disease due to Particulate Matter emissions; IRP = Potential Human exposure efficiency relative to U235; ETP-fw = Potential Comparative Toxic Unit for ecosystems; HTP-c = Potential Comparative Toxic Unit for humans – cancer effect; HTP-nc = Potential Comparative Toxic Unit for humans – non-cancer effect; SQP = Potential soil quality index													

Table 18 presents disclaimers which shall be declared in the project report and in the EPD with regard to the declaration of relevant core and additional environmental impact indicators according to the following classification. That can be declared in a footnote in the EPD.

Table 18: Classification of disclaimers to the declaration of core and additional environmental impact indicators

ILCD-classification	Indicator	disclaimer
ILCD-Type 1	Global warming potential (GWP)	none
	Depletion potential of the stratospheric ozone layer (ODP)	none
	Potential incidence of disease due to PM emissions (PM)	none
ILCD-Type 2	Acidification potential, Accumulated Exceedance (AP)	none
	Eutrophication potential, Fraction of nutrients reaching freshwater end compartment (EP-freshwater)	none
	Eutrophication potential, Fraction of nutrients reaching marine end compartment (EP-marine)	none
	Eutrophication potential, Accumulated Exceedance (EP-terrestrial)	none
	Formation potential of tropospheric ozone (POCP)	none
	Potential Human exposure efficiency relative to U235 (IRP)	1
ILCD-Type 3	Abiotic depletion potential for non-fossil resources (ADP-minerals&metals)	2
	Abiotic depletion potential for fossil resources (ADP-fossil)	2
	Water (user) deprivation potential, deprivation-weighted water consumption (WDP)	2
	Potential Comparative Toxic Unit for ecosystems (ETP-fw)	2
	Potential Comparative Toxic Unit for humans (HTP-c)	2
	Potential Comparative Toxic Unit for humans (HTP-nc)	2
	Potential Soil quality index (SQP)	2
Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.		
Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.		

Table 19: Parameters to describe the use of resources

Parameter	unit	A1-A3	A4	A5	B1	B2	B5	B6	B7	C1	C2	C3	C4	D
PERE	MJ, net calorific value													
PERM	MJ, net calorific value													
PERT	MJ, net calorific value													
PENRE	MJ, net calorific value													
PENRM	MJ, net calorific value													
PENRT	MJ, net calorific value													
SM	kg													
RSF	MJ, net calorific value													
NRSF	MJ, net calorific value													
FW	m ³													
Legend	<p>PERE = Renewable primary energy as energy carrier; PERM = Renewable primary energy resources as material utilization; PERT = Total use of renewable primary energy resources; PENRE = Non-renewable primary energy as energy carrier; PENRM = Non-renewable primary energy as material utilization; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of fresh water</p>													

Table 20: Parameters describing LCA-output flows and waste categories

Parameter	unit	A1-A3	A4	A5	B1	B2	B5	B6	B7	C1	C2	C3	C4	D
HWD	kg													
NHWD	kg													
RWD	kg													
CRU	kg													
MFR	kg													
MER	kg													
EEE	MJ													
EET	MJ													
Legend	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electric energy; EET = Exported thermal energy													

Table 21: Information describing the biogenic carbon content at the factory gate

Biogenic carbon content	Unit
Biogenic carbon content in product	kg C
Biogenic carbon content in accompanying packaging	kg C
NOTE 1 kg biogenic carbon is equivalent to 44/12 kg of CO ₂	

6 LCA: Interpretation

Content as defined in product specific PCR-B document.

7 Literature

Content as defined in product specific PCR-B document.

EN ISO 14040 Environmental management - Life cycle assessment -- Principles and framework

EN ISO 14044 Environmental management - Life cycle assessment -- Requirements and guidelines

EN ISO 14025 Environmental labels and declarations -Type III environmental declarations -- Principles and procedures

EN 15804 Sustainability of construction works - environmental product declarations. Core rules for the product category of construction products

General Principles and Guidelines Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report. Bau-EPD GmbH, in current version

8 Directory and Glossary

8.1 List of figures

none

8.2 List of tables

Table 1: technical data of the declared construction product(s).....	5
Table 2: Basic and auxiliary materials in mass percentage	5
Table 3: Reference service life (RSL)	6
Table 4: Declared unit.....	7
Table 5: Functional unit	7
Table 6: Declared life cycle stages	8
Table 7: Description of the scenario „Transport to building site (A4)“ x)	9
Table 8: Description of the scenario „Installation of the product in the building (A5)“	9
Table 9: Description of the scenario „maintenance (B2)“ based on table 9 in EN 15804	10
Table 10: Description of the scenario „repair (B3)“	10
Table 11: Description of scenario „replacement (B4)“	10
Table 12: Description of scenario „refurbishment (B5)“	10
Table 13: Description of scenarios „energy (B6)“ resp. „Water (B7)“	11
Table 14: Description of the scenario „Disposal of the product (C1 to C4)“	11
Table 15: Description of the scenario „re-use, recovery and recycling potential (module D)“	11
Table 16: Parameters to describe the environmental impact	12
Table 17: Additional environmental impact indicators.....	12
Table 18: Classification of disclaimers to the declaration of core and additional environmental impact indicators	13
Table 19: Parameters to describe the use of resources	14
Table 20: Parameters describing LCA-output flows and waste categories	15
Table 21: Information describing the biogenic carbon content at the factory gate	15

8.3 Abbreviations

8.3.1 Abbreviations as per EN 15804

EPD	environmental product declaration
PCR	product category rules
LCA	life cycle assessment
LCI	life cycle inventory analysis
LCIA	life cycle impact assessment
RSL	reference service life
ESL	estimated service life
EPBD	Energy Performance of Buildings Directive
GWP	global warming potential
ODP	depletion potential of the stratospheric ozone layer
AP	acidification potential of soil and water
EP	eutrophication potential
POCP	formation potential of tropospheric ozone
ADP	abiotic depletion potential

8.3.2 Abbreviations as per corresponding PCR

CE-mark	french: Communauté Européenne or Conformité Européenne = EC certificate of conformity
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals



Owner and Publisher

Bau EPD GmbH
Seidengasse 13/3
1070 Wien
Österreich

Tel +43 699 15 900 500
Mail office@bau-epd.at
Web www.bau-epd.at



Programme Operator

Bau EPD GmbH
Seidengasse 13/3
1070 Wien
Österreich

Tel +43 699 15 900 500
Mail office@bau-epd.at
Web www.bau-epd.at

Logo

Author of the Life Cycle Assessment

Name of creator in person
Name of Institution (if rel.)
Address
Postcode, Location
COUNTRY

Mail Person creator
Tel
Fax
Mail
Web

Logo

Holder of the declaration

Name of creator in person
Name of Institution (if rel.)
Address
Postcode, Location
COUNTRY

Tel
Fax
Mail
Web