

# PRODUCT CATEGORY RULES FOR BUILDING RELATED PRODUCTS AND SERVICES

as per ISO 14025 and EN 15804+A2

for preparation of EPDs (Environmental Product Declarations)  
according to the EPD programme of the BAU EPD GmbH



[www.bau-epd.at](http://www.bau-epd.at)

## Part B: Requirements on the EPD for Reinforcing steel

PCR-Code: 2.16.2.1

Date 2021-11-27



## Imprint

### Publisher:

Bau EPD GmbH

Seidengasse 13/3

A-1070 Vienna

Austria

<http://www.bau-epd.at>

[office@bau-epd.at](mailto:office@bau-epd.at)

© Bau EPD GmbH

Picture credits frontpage: [www.marienhuetten.at](http://www.marienhuetten.at)

### Tracking of versions

Version	Comments	Date of changes
1.0	PCR approved by PCR review panel and published for interested parties to comment	2019-03-29
2.0	PCR including comments of interested parties, checked and approved by PCR panel for EPD creation	2019-07-06
3.0	Adaptation as per EN 15804:2019+A2:2019; adaptation of rules for declaration of geographical representativity	2020-11-05
4.0	Public version for interested parties after approval of PCR review panel.	2021-01-12
5.0	Consideration of comments, approval for EPD creation	2021-04-07
6.0	Adaptation tables module B and C, minor editorial changes	2021-08-27
<b>7.0</b>	<b>Change ECO Platform logo, note to photographic rights, minor editorial changes (created by SR, checked and approved by FG</b>	<b>2021-11-27</b>

## Contents

1. Scope .....	5
Requirements on the layout of the EPD .....	5
Content of the EPD .....	5
1. General information .....	7
2. Product .....	9
2.1 General product description .....	9
2.2 Application field .....	9
2.3 Standards, guidelines and regulations relevant for the product .....	9
2.4 Technical data .....	10
2.5 Basic/auxiliary materials .....	11
2.6 Production .....	12
2.7 Packaging .....	13
2.8 Conditions of delivery .....	13
2.9 Transport .....	14
2.10 Processing/ installation .....	14
2.11 Use stage .....	14
2.12 Reference service life (RSL) .....	14
2.13 Reuse and recycling .....	15
2.14 Disposal .....	15
2.15 Further information .....	15
3. LCA: Calculation rules .....	16
3.1 Declared unit/ Functional unit .....	16
3.2 System boundary .....	16
3.3 Flow chart of processes/stages in the life cycle .....	17
3.4 Estimations and assumptions .....	18
3.5 Cut-off criteria .....	18
3.6 Data sources .....	18
3.7 Data quality .....	18
3.8 Reporting period .....	18
3.9 Allocation .....	18
3.10 Comparability .....	18
4. LCA: Scenarios and additional technical information .....	19
4.1 A1-A3 product stage .....	19
4.2 A4-A5 Construction process stage .....	19
4.3 B1-B7 use stage .....	20
4.4 C1-C4 End-of-Life stage .....	22
4.5 D Potential of reuse and recycling .....	22
5. LCA: results .....	23

6. LCA: Interpretation .....	27
7. Literature .....	28
8. Directory and Glossary .....	28
8.1 List of figures .....	28
8.2 List of tables .....	28
8.3 Abbreviations .....	29

## 1. Scope

This document contains the **Requirements on an Environmental Product Declaration (EPD)** as per EN 15804 and ISO 14025 and requirements of Bau EPD GmbH.

The document applies to:

Construction products made of steel in an unprocessed state that fulfill their function in connection with concrete (bars, rings, rolled goods, mats, wire mesh, connecting parts, etc.)

The requirements on the EPD include:

- Requirements from EN ISO 14025
- Requirements on the EN 15804 standard as a European core EPD
- Complementary requirements on EPD of Bau EPD GmbH

The calculation rules for the Life Cycle Assessment and Requirements on the project report are specified in a separate document – “Management System Handbook chapter 5” of Bau EPD GmbH.

## Requirements on the layout of the EPD

Bau-EPD GmbH determines the following features with regard to the layout of the EPD:

- The document on hand defines the format template for EPD-document that is to fill in (Word file „Format template EPD Bau EPD GmbH“, download at [www.bau-epd.at](http://www.bau-epd.at)).
- The content of an EPD is not limited in length of text.
- The layout of the front page of the EPD is defined and picture material must be accorded with Bau EPD GmbH (not more than 4 MB).
- On the last page of the EPD the publishing institution as well as the programme operator (Bau EPD GmbH in both cases), the LCA practitioner and owner of the declaration must be indicated with a logo and full address (including telephone number, fax number, email and website).
- Generally the font „Calibri“ must be used.
- In addition to the EPD as Microsoft Word format an Excel-document (BAU EPD M-DOCUMENT 8- excel-file for electronic data transfer Editor baubook ECO Platform) must be created including the result tables for electronic transfer and complying to EN 15942 (ITM Matrix). The templates of Bau EPD GmbH must be used, for these tables also serve to forward data to database owners (ECO Platform/ECO Portal, OEKOBAUDAT and BAUBOOK).

## Content of the EPD

The following format template respective guidance describes the required structure of the EPD document including the **required content for each individual chapter**.

In addition to that, this document is giving **specific notes for the creation of an EPD for reinforcing steel** and **specific LCA calculation rules for reinforcing steel** that must be considered when creating the EPD and underlying LCA study.

Parts of the content that are considered as additional information of optional character (=not required as per international standard and/or guidelines from ECO Platform) are marked in lilac colour. This information is free to choose whether to declare or not and indications can be delivered by the owner of the declaration on optional basis.

Legend:

- Blue: required content for each chapter
- Turquoise: specific requirements for EPD of materials from the scope of the PCR
- Green: specific LCA rules for EPD of material from the scope of the PCR
- Violet: additional information of optional character

# EPD - ENVIRONMENTAL PRODUCT DECLARATION

As per ISO 14025 and EN 15804



PUBLISHER	Bau EPD GmbH, A-1070 Wien, Seidengasse 13/3, <a href="http://www.bau-epd.at">www.bau-epd.at</a>
PROGRAMME OPERATOR	Bau EPD GmbH, A-1070 Wien, Seidengasse 13/3, <a href="http://www.bau-epd.at">www.bau-epd.at</a>
OWNER OF THE DECLARATION	Name of declaration owner
DECLARATION NUMBER	To be accorded with Bau EPD GmbH
ISSUE DATE	Date
VALID TO	Date
NUMBER OF DATASETS	Number

Name and description of product

Name of declaration owner

picture

To be accorded with declaration owner  
and Bau EPD GmbH

(Note: photographic rights must be  
clarified and cited)

Company logo of  
declaration owner

Contents:

<b>Content of the EPD .....</b>	<b>5</b>
1. General information .....	7
2. Product.....	9
2.1 General product description .....	9
2.2 Application field .....	9
2.3 Standards, guidelines and regulations relevant for the product .....	9
2.4 Technical data .....	10
2.5 Basic/auxiliary materials .....	11
2.6 Production .....	12
2.7 Packaging .....	13
2.8 Conditions of delivery .....	13
2.9 Transport .....	14
2.10 Processing/ installation.....	14
2.11 Use stage .....	14
2.12 Reference service life (RSL).....	14
2.13 Reuse and recycling .....	15
2.14 Disposal .....	15
2.15 Further information.....	15
3. LCA: Calculation rules .....	16
3.1 Declared unit/ Functional unit .....	16
3.2 System boundary .....	16
3.3 Flow chart of processes/stages in the life cycle .....	17
3.4 Estimations and assumptions.....	18
3.5 Cut-off criteria.....	18
3.6 Data sources .....	18
3.7 Data quality.....	18
3.8 Reporting period .....	18
3.9 Allocation .....	18
3.10 Comparability .....	18
4. LCA: Scenarios and additional technical information .....	19
4.1 A1-A3 product stage .....	19
4.2 A4-A5 Construction process stage .....	19
4.3 B1-B7 use stage.....	20
4.4 C1-C4 End-of-Life stage.....	22
4.5 D Potential of reuse and recycling .....	22
5. LCA: results.....	23
6. LCA: Interpretation.....	27
7. Literature.....	28
8. Directory and Glossary .....	28
8.1 List of figures.....	28
8.2 List of tables.....	28
8.3 Abbreviations.....	29

**1. General information**

<p><b>Product name</b> Name and description of product</p>	<p><b>Declared Product / Declared Unit</b> Description of the declared product and declared unit/functional unit</p>
<p><b>Declaration number</b> To be accorded with Bau EPD GmbH</p>	<p><b>Number of datasets in EPD Document(s):</b> XX</p>
<p><b>Declaration data</b>  <input type="checkbox"/> Specific data  <input type="checkbox"/> Average data</p>	<p><b>Range of validity</b> The products considered in the data of the life cycle assessment and for which the declaration applies must be named.</p>
<p><b>Declaration based on:</b> MS-HB version dated dd.mm.yyyy: Name of PCR PCR Code Version (PCR tested and approved by the independent expert committee = PKR-Gremium) The owner of the declaration is liable for the underlying information and evidence; Bau EPD GmbH is not liable with respect to manufacturer information, life cycle assessment data and evidence.</p>	<p>In the case of an average EPD, this type of EPD must be pointed out. The representativeness of the declaration must be shown with regard to the production volume covered by the life cycle assessment and the technology used. Likewise, the range of fluctuation of the product group considered, must be specified in the interpretation.</p>
<p><b>Type of Declaration as per EN 15804</b> From cradle to ... .. LCA-method: (i.e. Cut-off by classification)</p>	<p><b>Database, Software, Version</b> Declaration of background database, Software used and both its versions</p>
<p><b>Author of the Life Cycle Assessment</b> Name of the author Institution, Address website</p>	<p><b>The CEN standard EN 15804:2014+A1 serves as the core-PCR.</b> <b>Independent verification of the declaration according to ISO 14025:2010</b>   <input type="checkbox"/> internally      <input checked="" type="checkbox"/> externally   <b>Verifier 1:</b>      Name  <b>Verifier 2:</b>      Name</p>
<p><b>Owner of the Declaration</b> Name of the manufacturer/owner Institution, Address website</p>	<p><b>Publisher and Programme Operator</b> Bau EPD GmbH Seidengasse 13/3 1070 Vienna Austria</p>

DI (FH) DI DI Sarah Richter  
Managing director Bau EPD GmbH

DI Dr. sc ETHZ Florian Gschösser/ N.N.  
chairperson/vice chairperson of expert committee (PCR-Gremium)

Academic Title Name  
Verifier

Academic Title Name,  
Verifier

**Note:** EPDs from similar product groups from different programmes might not be comparable.



## 2. Product

### 2.1 General product description

For the product description the characteristics of the declared product must be described. In case of average EPD (“sector or branch” EPD) all declared products must be described separately.

Indications for the general product description:

- Separate description of products/materials for each product standard applicable, citing the product types and names.
- Description of characteristic components.
- All factory locations for the respective product categories must be declared, alternatively a reference can be made to an overview in an appendix (mandatory information in the project report, voluntary information in the EPD document)

#### Specific notes for the creation of an EPD for reinforcing steel:

Any explanation based on an example:

The declared product is e.g. one ton of reinforcing steel of a specific quality class according to ÖNORM B 4707 and DIN 488.

Example:

2.1.1 Reinforcing steel B550B according to ÖNORM B 4707 (ÖN EN 10080)

Rolled, heat treated and tempered B550B quality bar. Diameter from 8 to 40 mm. Factory length 14 m, special lengths according to agreement.

Rolled, heat treated and tempered B550B quality steel in coils. Diameter from 8 to 16 mm. Ring weight: 1.7 tons.

Rolled, heat treated, B550B quality steel in coils. Diameter from 8 to 16 mm. Ring weight: 3 and 5 to.

2.1.2 Reinforcing steel B500B according to DIN 488 (DIN EN 10080)

Rolled B500B quality bar, heat treated and tempered in-house. Diameter from 8 to 40 mm. Factory length 14 m, special lengths according to agreement.

Rolled, heat treated and tempered B500B quality steel in coils. Diameter from 8 to 16 mm. Ring weight: 1.7 tons.

Rolled, heat treated, B550B quality steel in coils. Diameter from 8 to 16 mm. Ring weight: 3 and 5 to.

### 2.2 Application field

The use and application purpose of the named products are to specify. The individual applications (including functions) must be declared as a text or table format.

#### Specific notes for the creation of an EPD for reinforcing steel:

None.

### 2.3 Standards, guidelines and regulations relevant for the product

The respective standard and/or general technical approval or comparable national regulation can be indicated.

Optional: Documentation under the frame of CE -certification such as certificates of constancy of performance, certificates of conformity of the internal production control on the manufacturer’s site, Declarations of performance, Official certificates of registration, European Technical Assessments or Technical permissions of construction industry can be cited.

#### Specific notes for the creation of an EPD for reinforcing steel:

The standards regulating reinforcing steel must be cited (i.e. standards, guidelines, other regulations)

Examples for product standards for reinforcing steel in Austria are illustrated in table 1.

Table 1: Product specific standards

Standard	Title
ÖNORM B 4707	Reinforcing steel - Requirements, classification and compliance
DIN 488	Rebar part 1-6
ÖNORM EN 10080	Steel for reinforcement of concrete - weldable rebar

## 2.4 Technical data

For products carrying a CE marking as per Construction Products Regulation (CPR) the EPD must declare at least the same technical data as required and indicated in the declaration of performance of the manufacturer. What kind of data is required in each individual case is to learn from the document underlying the CE marking: any Harmonized European Standard or European Technical Assessment (ETA). Additional technical data must be listed if relevant for product distinction or specification.

### Specific notes for the creation of an EPD for reinforcing steel:

The (structural) technical data listed in Table 2 are based on the national standards or the harmonized European product standards for reinforcing steel (see scope) and must be specified with reference to the test standard. An indication in the different categories is only to be made if these are relevant for the declared product according to the product standard (see footnotes). There is no harmonized European product standard for reinforcing steel (as of the creation of the PCR).

Table 2: Technical data of the declared construction

Table 2.1 Reinforcing steel B550B in bars and coils according to ÖNORM B4707 and ÖNORM EN 10080

Characterization	Value	Unit
density	7.85	kg/dm <sup>3</sup>
yield point (Re)	550	MPa
Proportional limit, 0.2% proof stress	550	MPa
Elongation (for B-ductility))	≥ 5	%
Rm/Re	Max. 1.3 x re	-
Mass per running meter (see ÖNORM B 4700, 2017-6 Table 5, or EN 10080)	Depending on the diameter	Kg/m
Fatigue strength (high voltage)	300	MPa
Stress range 2 σ <sub>a</sub> for 2 · 10 <sup>6</sup> load changes	for d < 20 mm : 150	MPa
	for 20 ≤ d < 36 mm : 120	MPa
	for d ≥ 36 mm : 100	MPa
Related rib area f <sub>R</sub>	for 8 mm < d ≤ 12 mm: 0,40	-
	for < 12 mm: 0,56	-
weldability	C ≤ 0,22 (0,24) P ≤ 0,050 (0,055) S ≤ 0,050 (0,055) N ≤ 0,012 (0,014) Cu ≤ 0,80 (0,85) C <sub>eq</sub> ≤ 0,50 (0,52)	

Table 2.2 Reinforcing steel B500B in bars and coils according to DIN 488 and DIN EN 10080

Characterization	Value	Unit
density	7,85	kg/dm <sup>3</sup>
yield point (Re)	500	MPa
Proportional limit, 0.2% proof stress	500	MPa
Elongation (for B-ductility))	≥ 5	%
Rm/Re	max. 1,3 x Re	-
Mass per running meter (see ÖNORM B 4700, 2017-6 Table 5, or EN 10080)	Je nach Durchmesser	Kg/m

Stress range $2\sigma_a$ in MPa at $1 \times 10^6$ load cycles; Voltage exponent $k_1$ and $k_2$ of the Wöhler curve (upper stress of $0.6 R_{e,nom}$ )	$d \leq 28,0$ mm: $175d$ $k_1 = 4d$ ; $k_2 = 9d$ $d > 28$ mm: $145$ $k_1 = 4$ ; $k_2 = 9$	
Related rib area $f_R$	$\varnothing 8$ mm: 0,045	-
	$\varnothing 9$ mm bis 10 mm: 0,052	-
	$\varnothing 11$ mm bis 40 mm: 0,056	-
weldability	$C \leq 0,22$ (0,24) $P \leq 0,050$ (0,055) $S \leq 0,050$ (0,055) $N \leq 0,012$ (0,014) $Cu \leq 0,60$ (0,65) $C_{eq} \leq 0,50$ (0,52)	

For specific EPD the technical data of the product must be declared as required in Table 2.

For average EPD (“Sector or Branch-EPD”, “Group EPD” or “EPD from Associations”) Table 2 must be filled, average values or ranges are accepted, in addition a note stating „see product sheets“ pointing to single technical product sheets can be cited. Technical data must be provided by the manufacturers. The manufacturers are to ensure that the relevant data are accessible, and the LCA-practitioner must indicate the sources where the technical data can be downloaded.

In this case the average value of nominal density/ weight per  $m^2$  used for calculating the LCA must be declared as an additional information in chapter 3.1.

## 2.5 Basic/auxiliary materials

The product components and/or contents and ingredients must be declared in mass-% to enable the user of the EPD to understand the composition and structure of the product in delivery status. These indications shall also support security and efficiency in installation, use and disposal of the product.

The declaration of mass-% can be accurate numbers or a range by analogy with REACH<sup>1</sup>. The mass of components that make up less than 1 mass-% of the total product mass can be declared with < 1 mass-%.

The declaration of material product content must list at least those substances contained in the product which are included in the “Candidate List of Substances of Very High Concern for Authorization” where their contents exceed the limit values (0.1 mass-% on product level) for registration by the European Chemicals Agency (ECHA<sup>2</sup>). If substances and preparations lose their hazardous features during manufacturing (e.g. after a complete chemical reaction) they are exempted from the obligation of declaration.

If the content of the material is below the limit of ECHA the following note must be stated in the EPD:

„The content of XXXX is below the limit values of the registration by the European Chemicals Agency (ECHA). Interpreting statements such as “... free of ...” or “... are entirely harmless ...” are not permissible.

The product components must be described in detail, so that their sort of product is clear, but the protection of sensitive data is assured, and company secrets are not revealed.

For additives, the function and substance class respective chemical group (i.e. hydraulic binders) must be stated. In addition to that all auxiliary materials and additives that stay within the product must be declared.

### Specific notes for the creation of an EPD for reinforcing steel:

Basic materials are to be listed according to Table 3, auxiliary materials are to be listed separately.

<sup>1</sup> Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

<sup>2</sup> European Chemicals Agency: <http://echa.europa.eu/de>

**Table 3: base materials in mass-% (example)**

Bestandteile:	Massen %
iron 1)	
carbon 2)	
silicon 3)	
manganese <sup>3)</sup>	
iron accompanying elements 4)	
Share of secondary steel/scrap input <sup>5)</sup>	

<sup>x)</sup> **Optional:** footnote with description for each component

- 1) Iron scrap, is melted in the furnace
- 2) carbon carriers, depending on the manufacturing method of the products
- 3) Silicon and manganese as an alloying element
- 4) usual by-elements of steel scrap, e.g. Cu,Cr,Ni
- 5) Use of scrap according to European scrap lists

**Auxiliaries / additives**  
Specifications and proportions of excipients are to be stated (in text or tabular format)

## 2.6 Production

The process of production must be described and illustrated with a simple figure (i.e. flow chart). In case of average EPD the production processes of all sites must be described respective a useful summary must be included and a list of all production sites must be provided in an annex. Quality management systems, eco management systems etc. can be referred to.


### Specific notes for the creation of an EPD for reinforcing steel:

Example:

For the Electric Arc Furnace production path, scrap is melted in an Electric Arc Furnace to obtain liquid steel. Refining (reduction of sulphur, phosphorus and other accompanying elements), alloying (e.g. about 1% Mn, 0.2% Si) and possibly micro-alloying (e.g. 0.01% V) are applied to give the steel its required properties to give properties.

At the end of steel production, the liquid steel is cast into a billet in a continuous caster. The semi-finished product is hot-rolled in a rolling mill to the end product with the corresponding finished diameter.

**Figure 1: Example of a flow chart/graphic production stage**



**Legend:**

Schrott	scrap metal
Elektrolichtbogenofen	electric arc furnace
Pfannenofen	ladle furnace
Strangguss	continuous casting
Stoßofen	pusher furnace
Vorstraße	fore road
Mittelstraße	middle road
Fertigblock	finished block
Tempcore-Anlage	Tempcore plant
Spulenanlage	winding system
Kühlbett	cooling bed

Description of chart

**2.7 Packaging**

Information concerning each component of packages:

- Type (Foil, pallets, etc.),
- Material (Paper, Polyethylene; including origin, e.g. recycled paper) and
- Possibilities of reuse (e.g. multi way pallets).

**Specific notes for the creation of an EPD for reinforcing steel;**

Example: As a rule, reinforcing steel is delivered loose (without packaging material) but sometimes with squared timber as a stacking aid and with steel wire fastening straps for bundling.

**2.8 Conditions of delivery**

Written description of conditions of delivery, units of delivery, size and dimension as well as requirements on storage important for the declared product(s).

## 2.9 Transport

Description of delivery (Route and means of transport).

## 2.10 Processing/ installation

Description of way of treatment, used machines, tools, dust collection etc., auxiliary materials as well as measures of noise reduction. Notes regarding recognized rules of engineering, work safety or protection of the environment can be included. References to detailed processing directives and referrals to user safety (safe use instruction sheets) of the manufacturer are required.

**Specific notes for the creation of an EPD for reinforcing steel:**

**The focus of this PKR is on rebars in their unprocessed condition.**

**The further processing of reinforcing steel can take place in 2 scenarios:**

- a) direct transport and processing (bending) at the construction site with subsequent installation
- b) Transport to a bending shop and processing (bending) in the bending shop with subsequent transport to the construction site and installation

**The flows of direct transport to the construction site (scenario a) or the flows of transport to the bending shop and the flows of processing in the bending shop and the flows of subsequent transport to the construction site (scenario b) must be balanced in A4-A5**

## 2.11 Use stage

Notes describing specific features of the material composition relevant for the use stage.

**Specific notes for the creation of an EPD for reinforcing steel:**

In the case of reinforcing steel products that are completely encased in concrete, there are no changes in the material composition over the period of use if they are properly planned, properly and professionally installed and are used without problems.

## 2.12 Reference service life (RSL)

The indication of the reference service life (RSL) is imperative for EPDs covering the complete use stage (modules B1-B7), or if a use stage scenario is described, which refers to the lifetime of the product (“from cradle to grave”).

The RSL must refer to the declared technical and functional quality of the product. It must be established in line with all of the specific rules in the European product standards and must also take consideration of the ISO 15686-1, -2, -7 and -8 standards.

Where information is available for deriving the RSL from harmonized European product standards, such data has priority.

The assumption underlying the calculation of the RSL and for those only the RSL can be declared must be stated. Influence on aging as per recognized rules of engineering.

**Table 4: Reference service life (RSL)**

Characterization	value	unit
Reinforcing steel 1)	100	years
		years
Reference conditions on which the RSL is based (if relevant)		Individual units

1)The prerequisite is standard-compliant maintenance in accordance with 2.11

See EN 15804+A2 clause 6.3.4 and Annex A requirements and guidelines for reference service life

If no reference service life can be determined according to the rules of EN 15804+A2 (Annex A), a default value from a complementary PCR of the CEN/TC product committees, if available, must be used. If no complementary PKR is available, the service life can be declared from service life catalogues, depending on the area of application, stating the source, e.g. according to BAU EPD-M-DOKUMENT-20-Reference-usage-times-20150810 (Austria) or the BBSR table "Useful lives of components on life cycle analysis according to BNB" (Germany). If no information can be found there, the RSL can be derived from other sets of regulations (Eurocodes, other basis).

### **2.13 Reuse and recycling**

Possibilities and scenarios of reuse and recycling must be described.

### **2.14 Disposal**

The different ways of disposal must be described.

The EAK-waste disposal code (Disposal code following the European list of waste) must be declared.

### **2.15 Further information**

Optional details, indication of reference source for additional information, e.g. websites...

### 3. LCA: Calculation rules

#### 3.1 Declared unit/ Functional unit

The declared resp. functional unit, the mass reference and the conversion factor to 1 kg must be declared in a table.

##### **Specific LCA calculation rules for reinforcing steel:**

The declared unit for reinforcing steel is 1 t without processing in an external bending shop. The average bulk density must be specified. Other declared units are permitted if the conversion to 1 t is shown transparently. In any case, the dimensions relevant to different applications and the density of the material must be specified.

**Table 5: Declared unit 1 t**

characterization	value	unit
Declared unit	1	t
Bulk density	7856	kg/m <sup>3</sup>

A functional unit can be specified for reinforcing steel if the function of the declared products can be clearly described.

If average results of different products are declared, the methods of calculating the average values must be explained.

In this case the average value of nominal density/ weight per unit used for calculating the LCA must be declared as an additional information.

#### 3.2 System boundary

The type of EPD with regard to the applied system boundaries must be specified in the EPD. All building products and materials must declare modules A1-A3, modules C1-C4 and module D. The following EPD types may be specified:

- from the cradle to the factory gate with modules C1-C4 and module D (A1-A3 + C + D);
- from the cradle to the factory gate with options, modules A1-A3, C1-C4 and D (A1-A3 + C + D and additional modules. The additional modules may be one or more modules selected from A4 to B7);
- from cradle to grave and module D (A + B + C + D)

Exceptions to this rule are specified in EN 15804+A2, chapter 5.2.

Note: The specifications for the modules that must be declared no longer correspond to ÖNORM EN 16783:2017 - the specifications from EN 15804:2019+A2 apply primarily.

All declared life cycle stages (modules) are to be marked with an "X" in Table 7. Undeclared modules are to be marked with ND (= not declared).



Table 6: Declared life cycle stages

PRODUCT STAGE			CON-STRUCTION PROCESS STAGE		USE STAGE							END-OF-LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Construction, installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction, demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x

X = included in LCA; MND = Module not declared

The modules assessed in the LCA study must be described shortly. It should be made apparent, which processes are calculated in which module and how the system boundaries to nature resp. to other product systems are set (if relevant for the declared product).

If not all modules are declared in an EPD, a clear justification must be given.

**Specific LCA calculation rules for reinforcing steel:**

**A1-A3:**

In the manufacturing phase, all materials, products and energies (including energy export) as well as any waste and its treatment or disposal must be taken into account. Modules A1, A2 and A3 can be evaluated and presented in aggregated form.

**A4-A5:**

In the construction phase, all transport routes (possible transport to bending shops and transport to the construction site) as well as the energy that occurs for the bending process) must be taken into account.

**B1-B7:**

As a rule, no LCA-relevant processes occur over the period of use with reinforcing steel embedded in concrete.

For all other product applications, the maintenance work must be accounted for in accordance with 2.11.

**C1 - C4 and D:**

Reinforced steel, which is recovered in the course of concrete recycling, can in principle be fed into a recycling process.

The recycling scenario must therefore be balanced for the disposal phase.

**3.3 Flow chart of processes/stages in the life cycle**

A meaningful flow chart describing the manufacturing process shall give further aid to comprehension. The flow chart must be subdivided at least into the phases of life cycle declared (production, use, end-of-life). The phases can be partitioned into appropriate process stages.

### 3.4 Estimations and assumptions

The assumptions and assessments that are important for the interpretation of the life cycle assessment are to be listed here.

### 3.5 Cut-off criteria

The application of the cut-off criteria according to MS-HB Chapter 5.5.3 must be documented here.

### 3.6 Data sources

The quality of the collected data must be described.

### 3.7 Data quality

The sources of the background data sets must be declared. If necessary, additional information on the quality of the used data sets shall be made (estimations). The issuing year of the used data material must be indicated.

### 3.8 Reporting period

The period under review must be documented (in case of average EPD this would be the basis of the calculated average).

### 3.9 Allocation

The allocations of relevance for calculation (appropriation of expenses across various products) must be indicated, at least:

- System boundary settings/allocation in the use of recycled and/or secondary raw materials
- Allocation concerning co-products
- Allocation of energy, auxiliary and operating materials used for individual products in a factory
- Loads and credits from recycling or energy recovery of packaging materials and production waste
- Loads and credits from recycling or energy recovery from the end of life of the product

whereby reference must be made to the modules in which the allocations are performed.

Detailed regulations concerning calculation of secondary materials and allocation MS-HB chapter "LCA rules" apply in all studies.

#### **Specific LCA calculation rules for reinforcing steel:**

According to EN 15804, an economic allocation must be used for "slag", "scale" and "district heating". The loads from granulation, dewatering and transport of these products are 100% attributable to them. Deviations from this rule shall be justified in terms of their compliance with EN 15804."

In addition, a mass allocation is carried out for modules C1-C3. The components of 1m<sup>3</sup> reinforced concrete are divided into their shares (reinforcing steel and concrete) and weighted accordingly in the balance.

### 3.10 Comparability

With reference to comparability of EPD data the following facts must be mentioned:

Comparison or benchmarking of EPD data is only possible, if all compared data sets are calculating following EN 15804, the same programme specific PCR-rules or other additional rules. The same background data sources and software versions must be applied. Moreover, the context of the function in the building or product specific features of performance must be considered.

## 4. LCA: Scenarios and additional technical information

The following information is mandatory to give for all declared modules, for modules not declared it is optional. If need, additional information can be declared.

### 4.1 A1-A3 product stage

Following EN 15804 no scenario documentation is required for A1-A3 for the declaration and calculation of these modules lies within the responsibility of the manufacturer and must not be altered by the LCA practitioner.

Note: the masses of packaging per declared unit must be indicated, this is especially important if A5 is not declared.

### 4.2 A4-A5 Construction process stage

Table 9 and the units listed must be used for calculation the environmental impact of the transport phase.

Table 10 and the units listed must be used for calculation the environmental impact of the installation into the building.

**Table 7: Description of the scenario „Transport to building site (A4)“**

Parameters to describe the transport to the building site (A4)	Quantity per unit
Average transport distance	km
vehicle type, Commission Directive 2007/37/EC (European Emission Standard)	-
Fuel type and average consumption of vehicle	l/100 km
Maximum transport mass	tons
Capacity utilisation (including empty returns)	%
Bulk density of transported products	kg/m <sup>3</sup>
Volume capacity utilisation factor (factor: =1 or <1 or ≥ 1 for compressed or nested packaged products)	-

x) The table must be filled with reference to the information available from the datasets used (i.e. in case of transport by ship). The datasets used must be noted in a footnote.

**Table 8: Description of the scenario „Installation of the product in the building (A5)“ as per table 8 in ÖNORM EN 15804**

Parameters to describe the installation of the product in the building (A5)	Quantity per unit
Ancillary materials for installation (specified by material);	Meaningful unit
Water use	m <sup>3</sup>
Other resource use	kg
Electricity demand	kWh or MJ
Other energy carrier(s): .....	kWh or other unit (e.g. litres)
Wastage of materials on the building site before waste processing, generated by the product’s installation (specified by type)	kg
Output materials (specified by type) as result of waste processing at the building site e.g. of collection for recycling, for energy recovery, disposal (specified by route)	kg
Direct emissions to ambient air, soil and water	kg

### 4.3 B1-B7 use stage

Reference Service life: [a]

The parameters and the units listed in the following tables must be used for calculation the environmental impact of the use stage (B2-B7). The tables can be excluded if no input or output happens. In this case a note of explanation would be sufficient: “In module BX-BY no material resp. mass flows occur, input +/- output = 0

**Table 9: Description of the scenario „maintenance (B2)“ based on table 9 in EN 15804**

Parameters maintenance (B2)	value	unit
Maintenance process		Description or source where description can be found
Maintenance cycle		Number per RSL or year <sup>a</sup>
Ancillary materials for maintenance, e.g. cleaning agent, specify materials		kg/cycle
Waste material resulting from maintenance (specify materials)		kg
Net fresh water consumption during maintenance		m <sup>3</sup>
Energy input during maintenance, e.g. vacuum cleaning, energy carrier type, e.g. electricity, and amount, if applicable and relevant		kWh

**Table 10: Description of the scenario „repair (B3)“**

Parameters repair (B3)	value	unit
Repair process		Description or source where description can be found
Inspection process		Description or source where description can be found
Repair cycle		Number per RSL or year
Ancillary materials, e.g. lubricant, specify materials		Kg or kg/cycle
Waste material resulting from repair, (specify materials)		kg
Net fresh water consumption during repair		m <sup>3</sup>
Energy input during repair, e.g. crane activity, energy carrier type, e.g. electricity, and amount		kWh

**Table 11: Description of scenario „replacement (B4)“**

Parameters replacement (B4)	value	unit
Replacement cycle		Number per RSL or year
Energy input during replacement e.g. crane activity, energy carrier type, e.g. electricity and amount if applicable and relevant		kWh
Exchange of worn parts during the product’s life cycle, e.g. zinc galvanised steel sheet, specify materials		kg

**Table 12: Description of scenario „refurbishment (B5)“**

Parameters refurbishment (B5)	value	unit
Refurbishment process		Description or source where description can be found
Refurbishment cycle		Number per RSL or year
Energy input during refurbishment e.g. crane activity, energy carrier type, e.g. electricity, and amount if applicable and relevant		kWh
Material input for refurbishment, e.g. bricks, including ancillary materials for the refurbishment process e.g. lubricant, (specify materials)		kg or kg / cycle
Waste material resulting from refurbishment (specify materials)		kg
Further assumptions for scenario development, e.g. frequency and time period of use, number of occupants		Units as appropriate

**Table 13: Description of scenarios „energy (B6)“ resp. „Water (B7)“**

Parameters energy (B6) and water (B7)	value	unit
Ancillary materials, e.g. lubricant, specify materials		Kg or kg/cycle
Net fresh water consumption		m <sup>3</sup>
Type of energy carrier, e.g. electricity, natural gas, district heating		kWh or m <sup>3</sup>
Power output of equipment		kW

Characteristic performance, e.g. energy efficiency, emissions, variation of performance with capacity utilisation etc.		units as appropriate
Further assumptions for scenario development, e.g. frequency and period of use, number of occupants		units as appropriate

**Specific LCA calculation rules for reinforcing steel:**

In the use phase (B1), there are no material and energy flows relevant to the life cycle assessment for reinforcing steel that is encased in concrete (i.e. the results for B1 are to be set at "zero").

During use, no maintenance, repair, replacement or conversion processes take place for rebars encased in concrete, which is why modules B2 to B5 cause no environmental impact (i.e. the results for B2 are to be considered "zero").

Modules B4 to B7 are not relevant for steel construction products, which also does not cause any environmental impact (B4 to B7 are to be declared with "0").

**4.4 C1-C4 End-of-Life stage**

Short description of processes concerning disposal and scenarios going with that (i.e. for transport).

**Specific LCA calculation rules for reinforcing steel:**

In principle, dismantled building products made of reinforcing steel are fed into a recycling process.

**Table 14: Description of the scenario „Disposal of the product (C1 to C4)“ according to table 12 in EN 15804**

Parameters for End-of-Life stage (C1-C4)	value	Quantity per m <sup>3</sup> insulation material
Collection process specified by type		kg collected separately
		kg collected with mixed construction waste
Recovery system specified by type		kg for re-use
		kg for recycling
		kg for energy recovery
Disposal specified by type		kg product or material for final deposition
Assumptions for scenario development, e.g. transportation		Appropriate units

**4.5 D Potential of reuse and recycling**

Short description of assumptions for reuse-, recover- and recycling processes.

**Specific LCA calculation rules for reinforcing steel:**

According to the assumed end-of-life scenario, Module D shows the recycling process for steel and the avoided environmental pollution for its new production.

The amount of this flow corresponds to the net flow amount according to EN 15804, 6.4.3.3.

Calculation of the net flow: All output flows of steel from B1 to C4 are added; from this the amounts of steel are subtracted, which are supplied as scrap in the manufacturing processes (modules A, B and C).

This applies under the condition that the quality of the scrap produced is comparable to the scrap quality in the input.

Note 1: Scrap enters the system without polluting the environment.

Note 2: Scrap generated within A1-A3 is either allocated as co-products or can be returned within A1-A3. When looping, the amount of scrap to be subtracted in the net flow calculation is reduced.

Note 3: In the case of products made from pure secondary material: When processing recyclate into a product, it can happen that more recyclate mass is used than product mass is produced. In this case, these environmental impacts must be declared as additional

information in the background report (the declaration in the EPD is voluntary). The environmental impact for this additional requirement in the input must be assumed as a positive numerical value (impact) for the environmental impact of the production of primary material and can be declared in Module D or in an additional table.

**Table 15: Description of the scenario „re-use, recovery and recycling potential (module D)“**

(Substituted primary materials resp. technologies must be declared in a separate footnote (including technical information).

Parameters for module D	value	unit
Materials for reuse, recovery or recycling from A4-A5		%
Energy recovery or secondary fuels from A4-A5		MJ/t resp. kg/t
Materials for reuse, recovery or recycling from B2-B5		%
Energy recovery or secondary fuels from B2-B5		MJ/t resp. kg/t
Materials for reuse, recovery or recycling from C1-C4		%
Energy recovery or secondary fuels from C1-C4		MJ/t resp. kg/t

## 5. LCA: results

The declaration of environmental indicators must be listed in the following tables with reference only to the declared life cycle stages. Indicator values should be declared with three valid digits (eventually exponential form (e.g. 1.23E-5 = 0.0000123)). A uniform format should be used for all values of one indicator. It is preferred that the definitions of the environmental indicators are spelled out completely to ensure the best possible readability. If space is needed in case of too many columns the defined abbreviations are accepted.

**Table 16: Parameters to describe the environmental impact of mineral insulating products per declared/functional unit**

Parameter	unit	A1-A3	A4	A5	B1	B2	B5	B6	B7	C1	C2	C3	C4	D
GWP total	kg CO <sub>2</sub> eq.													
GWP fossil fuels	kg CO <sub>2</sub> eq.													
GWP biogenic	kg CO <sub>2</sub> eq.													
GWP luluc	kg CO <sub>2</sub> eq.													
ODP	kg CFC-11 eq.													
AP	mol H <sup>+</sup> eq.													
EP freshwater	kg PO <sub>4</sub> <sup>3-</sup> eq.													
EP marine	kg N eq.													
EP terrestrial	mol N eq.													
POCP	kg NMVOC eq.													
ADPE	kg Sb eq.													
ADPF	MJ H <sub>u</sub>													
WDP	m <sup>3</sup> Welt eq. entz.													
Legende	GWP = Global warming potential; luluc = land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP = Eutrophierungspotenzial; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources WDP = Water (user) deprivation potential, deprivation-weighted water consumption													

Table 17: Additional environmental indicators

Parameter	Unit	A1-A3	A4	A5	B1	B2	B5	B6	B7	C1	C2	C3	C4	D
PM	disease incidence													
IRP	kBq U235 eq.													
ETP-fw	CTUe													
HTP-c	CTUh													
HTP-nc	CTUh													
SQP	dimension-less													
Legende	PM = Potential incidence of disease due to Particulate Matter emissions; IRP = Potential Human exposure efficiency relative to U235; ETP-fw = Potential Comparative Toxic Unit for ecosystems; HTP-c = Potential Comparative Toxic Unit for humans – cancer effect; HTP-nc = Potential Comparative Toxic Unit for humans – non-cancer effect; SQP = Potential soil quality index													



Table 18: Parameters to describe the use of resources of mineral insulating products per declared/functional unit

Parameter	unit	A1-A3	A4	A5	B1	B2	B5	B6	B7	C1	C2	C3	C4	D
PERE	MJ, net calorific value													
PERM	MJ, net calorific value													
PERT	MJ, net calorific value													
PENRE	MJ, net calorific value													
PENRM	MJ, net calorific value													
PENRT	MJ, net calorific value													
SM	kg													
RSF	MJ, net calorific value													
NRSF	MJ, net calorific value													
FW	m <sup>3</sup>													
Legend	PERE = Renewable primary energy as energy carrier; PERM = Renewable primary energy resources as material utilization; PERT = Total use of renewable primary energy resources; PENRE = Non-renewable primary energy as energy carrier; PENRM = Non-renewable primary energy as material utilization; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of fresh water													

contains restrictions that must be declared according to the following classification in the project report and in the EPD with regard to the declaration of relevant core and additional environmental impact indicators.

Table 19 contains restrictions that must be declared according to the following classification in the project report and in the EPD with regard to the declaration of relevant core and additional environmental impact indicators.

Table 19: Classification of disclaimers to the declaration of core and additional environmental impact indicators

ILCD-classification	Indicator	Disclaimer
ILCD-Type 1	GWP Global Warming Potential	none
	ODP Ozone Depletion Potential	none
	PM Particulate Matter	none
ILCD-Type 2	Acidification potential, Accumulated Exceedance (AP)	none
	Eutrophication potential, Fraction of nutrients reaching freshwater end compartment (EP-freshwater)	none
	Eutrophication potential, Fraction of nutrients reaching marine end compartment (EP-marine)	none
	Eutrophication potential, Accumulated Exceedance (EP-terrestrial)	none
	Formation potential of tropospheric ozone (POCP)	none
	Potential Human exposure efficiency relative to U235 (IRP)	1
ILCD-Type 3	Abiotic depletion potential for non-fossil resources (ADP-minerals&metals)	2
	Abiotic depletion potential for fossil resources (ADP-fossil)	2
	Water (user) deprivation potential, deprivation-weighted water consumption (WDP)	2
	Potential Comparative Toxic Unit for ecosystems (ETP-fw)	2
	Potential Comparative Toxic Unit for humans (HTP-c)	2
	Potential Comparative Toxic Unit for humans (HTP-nc)	2
	Potential Soil quality index (SQP)	2
Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.		
Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.		

**Table 20: Parameters describing LCA-output flows and waste categories of mineral insulating products per declared/functional unit**

Parameter	unit	A1-A3	A4	A5	B1	B2	B5	B6	B7	C1	C2	C3	C4	D
HWD	kg													
NHWD	kg													
RWD	kg													
CRU	kg													
MFR	kg													
MER	kg													
EEE	MJ													
EET	MJ													
Legend	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electric energy; EET = Exported thermal energy													

**Table 21: Information for description biogenic carbon content at factory gate**

Biogenic carbon content	unit
Biogenic carbon content in the product	kg C
Biogenic carbon content of packing	kg C
Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO <sub>2</sub>	

If the mass of biogenic carbon containing materials in the product is less than 5 % of the mass of the product, the declaration of biogenic carbon content may be omitted.

If the mass of biogenic carbon containing materials in the packaging is less than 5 % of the total mass of the packaging, the declaration of the biogenic carbon content of the packaging may be omitted.

## 6. LCA: Interpretation

For better understanding of the LCA, the aggregated indicators of the inventory analysis as well as those of the impact assessment (LCIA) from chapter 5 must be interpreted in a dominance analysis. The interpretation must describe a range resp. variance of LCIA results, if the EPD is valid for more than one product.

It is recommended to illustrate the results with graphic elements (i.e. the dominance analysis showing distribution of environmental impacts over several modules...)

When declaring average products, the range of possible results for the individual products for the main impact categories that are relevant to the materials used must be specified.

As for module D, the interpretation must declare, that the benefits and loads lie beyond the system boundary. Any graphic elements showing result interpretation of the life cycle must be created in a way, that modules A1-C4 and module D are displayed separate picture elements. Alternatively, the results can be interpreted without graphic elements.

### Extension of an EPD:

**It is mandatory to declare in a separate block in the project report:**

**Reasons for deviations of results of single indicators of more than 15% compared to the results before. This serves as an information for verifiers and enhances legal compliance. Users of the data can be informed of such facts.**

**Claims that can be published (i.e. same framework conditions, different electricity mix) can be declared in the EPD, if desired.**

## 7. Literature

Relevant standards and sources for the preparation of the EPD resp. for the definition of the product must be listed here. The full documentation of references is to be done as follows:

- Author, First name. and Author, First name. (year). Title of article. subtitle. location: publishing company.
- Author, First name. (year). Title of article. In: Surname, First name. and Surname, First name. (Publishing company): Name of paper. Bd. 2 or year number, 207-210.
- Organisation (Year): Full name of standard or rule. Date of Issue. Location. Legal institution.

Always to be quoted:

- ÖNORM EN ISO 14040 Environmental management - Life cycle assessment -- Principles and framework
- ÖNORM EN ISO 14044 Environmental management - Life cycle assessment -- Requirements and guidelines
- ÖNORM EN ISO 14025 Environmental labels and declarations -Type III environmental declarations -- Principles and procedures
- ÖNORM EN 15804 Sustainability of construction works - environmental product declarations. Core rules for the product category of construction products
- Management system handbook including applicable documents from Bau EPD GmbH

## 8. Directory and Glossary

### 8.1 List of figures

Figure 1: Example of a flow chart/graphic production stage .....	12
--	----

### 8.2 List of tables

Table 1: Product specific standards .....	10
Table 2: Technical data of the declared construction .....	10
Table 3: base materials in mass-% (example) .....	12
Table 4: Reference service life (RSL) .....	14
Table 5: Declared unit 1 t.....	16
Table 6: Declared life cycle stages .....	17
Table 7: Description of the scenario „Transport to building site (A4)“ .....	20
Table 8: Description of the scenario „Installation of the product in the building (A5)“ as per table 8 in ÖNORM EN 15804....	20
Table 9: Description of the scenario „maintenance (B2)“ based on table 9 in EN 15804 .....	20
Table 10: Description of the scenario „repair (B3)“ .....	21
Table 11: Description of scenario „replacement (B4)“ .....	21
Table 12: Description of scenario „refurbishment (B5)“ .....	21
Table 13: Description of scenarios „energy (B6)“ resp. „Water (B7)“ .....	21
Table 14: Description of the scenario „Disposal of the product (C1 to C4)“ according to table 12 in EN 15804 .....	22
Table 15: Description of the scenario „re-use, recovery and recycling potential (module D)“ .....	23
Table 16: Parameters to describe the environmental impact of mineral insulating products per declared/functional unit .....	23
Table 17: Additional environmental indicators.....	24
Table 18: Parameters to describe the use of resources of mineral insulating products per declared/functional unit .....	25
Table 19: Classification of disclaimers to the declaration of core and additional environmental impact indicators .....	26
Table 20: Parameters describing LCA-output flows and waste categories of mineral insulating products per declared/functional unit .....	27
Table 21: Information for description biogenic carbon content at factory gate .....	27

## 8.3 Abbreviations

### 8.3.1 Abbreviations as per ÖNORM EN 15804

EPD	environmental product declaration
PCR	product category rules
LCA	life cycle assessment
LCI	life cycle inventory analysis
LCIA	life cycle impact assessment
RSL	reference service life
ESL	estimated service life
EPBD	Energy Performance of Buildings Directive
GWP	global warming potential
ODP	depletion potential of the stratospheric ozone layer
AP	acidification potential of soil and water
EP	eutrophication potential
POCP	formation potential of tropospheric ozone
ADP	abiotic depletion potential

### 8.3.2 Abbreviations as per PCR on hand

CE-mark	french: Communauté Européenne or Conformité Européenne = EC certificate of conformity
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals



**Publisher**

Bau EPD GmbH  
Seidengasse 13/3  
1070 Wien  
Österreich

Tel +43 699 15 900 500  
Mail office@bau-epd.at  
Web www.bau-epd.at



**Programme Operator**

Bau EPD GmbH  
Seidengasse 13/3  
1070 Wien  
Österreich

Tel +43 699 15 900 500  
Mail office@bau-epd.at  
Web www.bau-epd.at

Logo

**Author of the Life Cycle Assessment**

Name of creator in person  
Name of Institution (if rel.)  
Address  
Postcode, Location

Mail Person creator  
Tel  
Fax  
Mail  
Web

Logo

**Owner of the declaration**

Name of creator in person  
Name of Institution (if rel.)  
Address  
Postcode, Location

Tel  
Fax  
Mail  
Web